Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2023	PDZXL02.9020	2.925	Diesel	8000					
SPECIAL	FEATURES & EMISSION C	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
Exhau	non Rail Direct Injection st Gas Recirculation, E Module, Diesel Oxidatio	lectronic Control	Loader, Tractor, Dozer, Materi	al Handler					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION				EXHAUST (g/kw-ł	OPACITY (%)				
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
37 ≤ kW < 56	Tier 4 Final	STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			3.7	0.03	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this <u>19th</u> day of May 2022.

Johns Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division

 Attachment: Engine Models
 EO #:
 U-R-013-0677
 Family:
 PDZXL02.9020
 Attachment Last Revised:
 4/26/2022

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fu	el	Peak Torque -	Peak Torque -	Peak Torque -	Peak Torque -				
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Fuel	Fuel Units	OBD	GHG	Special	Notes
TD2.9L4	C4DI55C		L4	2.925	Liters	74.2	horsepower	2300	29.7	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55,4		L4	2.925	Liters	74.2	horsepower	2600	32.4	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55A		L4	2.925	Liters	74.2	horsepower	2500	31.4	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55B		L4	2.925	Liters	74.2	horsepower	2400	30.3	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI54		L4	2.925	Liters	72.4	horsepower	2200	28.3	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50		L4	2.925	Liters	67.0	horsepower	2600	30.9	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50A		L4	2.925	Liters	67	horsepower	2500	28.8	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50C		L4	2.925	Liters	67	horsepower	2300	27.5	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI49		L4	2.925	Liters	65.7	horsepower	2200	26.3	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45		L4	2.925	Liters	60.3	horsepower	2600	29.4	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45A		L4	2.925	Liters	60.3	horsepower	2500	26.6	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45B		L4	2.925	Liters	60.3	horsepower	2200	24.7	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DT54		L4	2.925	Liters	72.4	horsepower	2200	28.5	lb/hr	191.7	lb-ft	1800	21.6	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DT50		L4	2.925	Liters	67	horsepower	2200	26.6	lb/hr	191.7	lb-ft	1800	21.5	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DT45		L4	2.925	Liters	60.3	horsepower	2200	24.1	lb/hr	179.9	lb-ft	1800	22.7	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45F		L4	2.925	Liters	60.3	horsepower	2200	24.7	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45E		L4	2.925	Liters	60.3	horsepower	2500	26.6	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI45D		L4	2.925	Liters	60.3	horsepower	2600	29.4	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI49A		L4	2.925	Liters	65.7	horsepower	2200	26.3	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50G		L4	2.925	Liters	67	horsepower	2300	27.5	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50E		L4	2.925	Liters	67	horsepower	2500	28.8	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI50D		L4	2.925	Liters	67	horsepower	2600	30.9	lb/hr	172.5	lb-ft	1800	22.4	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI54A		L4	2.925	Liters	72.4	horsepower	2200	28.3	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55G		L4	2.925	Liters	74.2	horsepower	2300	29.7	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55F		L4	2.925	Liters	74.2	horsepower	2400	30.3	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55E		L4	2.925	Liters	74.2	horsepower	2500	31.4	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55D		L4	2.925	Liters	74.2	horsepower	2600	32.4	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI55K		L4	2.925	Liters	74.2	horsepower	2600	32.4	lb/hr	191.7	lb-ft	1800	24.9	lb/hr	N/A	N/A	N/A	N/A
TD2.9L4	C4DI36EU		L4	2.925	Liters	48.8	horsepower	2200	20.5	lb/hr	183.6	lb-ft	1350	18.4	lb/hr	N/A	N/A	N/A	N/A