Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2023	PDZXL03.6060	3.621	Diesel	8000			
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
Charge Electi	non Rail Direct Injection Air Cooler, Exhaust G ronic Control Module, D yst, Selective Catalytic	as Recirculation, Diesel Oxidation	Loader, Tractor, Dozer, Pump, Compressor, Material Handler				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)				OPACITY (%)			
POWER CLASS	STANDARD CATEGORY			NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final	STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.001	0.31		0.1	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the $56 \le kW < 130$ power categories in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this <u>19th</u> day of May 2022.

Johna Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-013-0685 Family: PDZXL03.6060

Displacement Peak Power -Peak Power Peak Power Peak Power - Fuel Peak Torque - Peak Torque -Peak Torque -Peak Torque -Config Model Code Trim Displacement Units Peak Power Units Speed (rpm) Fueling Units Peak Torque Units Speed (rpm) Fuel Fuel Units OBD GHG Special Notes TCD3.6L4 CFXI100D L4 3.621 Liters 134.1 horsepower 2000 50.2 lb/hr 500 N-m 1600 40.7 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI100C L4 3.621 Liters 134.1 horsepower 2200 52 lb/hr 500 N-m 1600 40.7 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI100U L4 3.621 Liters 134.1 2300 52.8 lb/hr 500 N-m 1600 40.7 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXI95BU L4 3.621 Liters 127.3 2000 47.5 lb/hr 500 1600 40.7 lb/hr N/A horsepower N-m N/A N/A N/A TCD3.6L4 CEXI95AU L4 3.621 127.3 2200 49.3 lb/hr 500 N-m 1600 40.7 lb/hr N/A N/A N/A Liters horsepower N/A TCD3.6L4 CFXI95U L4 3.621 Liters 127.3 horsepower 2300 50.2 lb/hr 500 N-m 1600 40.7 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI70U L4 3.621 Liters 93.8 horsepower 2200 35.7 lb/hr 390 N-m 1600 31.1 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI74BU L4 3.621 Liters 99.7 horsepower 2000 36.3 lb/hr 410 N-m 1600 32.7 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI74AU L4 3.621 Liters 99.7 2200 37.6 lb/hr 410 1600 32.7 lb/hr N/A N/A N/A N/A horsepower N-m TCD3.6L4 CFXI74U L4 3.621 Liters 99.7 2300 39.2 lb/hr 410 N-m 1600 32.7 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXI80BU L4 3.621 107.2 2000 40 lb/hr 430 1600 34.9 lb/hr N/A N/A N/A Liters horsepower N-m N/A TCD3.6L4 CFXI80AU L4 3.621 Liters 107.2 horsepower 2200 41.8 lb/hr 430 N-m 1600 34.9 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI80U L4 3.621 Liters 107.2 horsepower 2300 43.2 lb/hr 430 N-m 1600 34.9 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI85BU L4 3.621 Liters 113.9 2000 42.4 lb/hr 460 N-m 1600 37.3 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXI85AU L4 3.621 113.9 2200 44.2 lb/hr 460 1600 37.3 lb/hr N/A N/A N/A Liters horsepower N-m N/A TCD3.6L4 CFXI85U 14 3.621 113.9 2300 45.5 lb/hr 460 N-m 1600 37.3 lb/hr N/A N/A N/A N/A Liters horsepower TCD3.6L4 CFXI90BU L4 3.621 Liters 120.6 horsepower 2000 44.9 lb/hr 480 N-m 1600 39 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXI90AU L4 3.621 120.6 2200 46.5 lb/hr 480 1600 39 lb/hr N/A N/A N/A N/A Liters horsepower N-m TCD3.6L4 CFXI90U L4 3.621 Liters 120.6 horsepower 2300 47.8 lb/hr 480 N-m 1600 39 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT100U L4 3.621 Liters 134.1 2200 52.7 lb/hr 500 N-m 1600 40.8 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXT95U L4 500 40.8 3.621 Liters 127.3 2200 49.3 lb/hr 1600 lb/hr N/A N/A N/A N/A horsepower N-m 500 40.8 TCD3.6L4 CFXT92U L4 3.621 Liters 123.3 2200 47.6 lb/hr N-m 1600 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXT85U L4 3.621 Liters 114.5 horsepower 2200 43.5 lh/hr 480 N-m 1600 38 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT77U L4 3.621 Liters 103.2 2200 40 lb/hr 440 N-m 1600 35.1 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CFXT75U L4 3.621 Liters 99.9 horsepower 2200 39.1 lb/hr 420 N-m 1600 33.7 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT69U L4 3.621 Liters 93.1 horsepower 2200 35.6 lb/hr 397 N-m 1600 31.6 lb/hr N/A N/A N/A N/A TCD3.6L4 CEXT88U L4 3.621 Liters 117.9 horsepower 2200 45.9 lb/hr 500 1600 40.8 lb/hr N/A N/A N-m N/A N/A L4 3.621 42.5 476 37.3 lb/hr N/A TCD3.6L4 CFXT83U Liters 111.2 horsepower 2200 lb/hr N-m 1600 N/A N/A N/A TCD3.6L4 CFXT70U L4 3.621 Liters 93.8 horsepower 2200 36.1 lb/hr 397 N-m 1600 31.6 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT61U L4 3.621 Liters 83.8 horsepower 2200 33.2 lb/hr 360 N-m 1600 29.1 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT68U L4 3.621 Liters 93.1 horsepower 2200 35.6 lb/hr 397 N-m 1600 31.6 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT74U L4 3.621 99.9 39.1 420 1600 33.7 lb/hr N/A 2200 lb/hr N/A N/A N/A Liters horsepower N-m 103.2 40 440 35.1 lb/hr TCD3.6L4 CFXT76U L4 3.621 Liters 2200 lb/hr 1600 N/A N/A N/A horsepower N-m N/A TCD3.6L4 CFXT82U L4 3.621 Liters 111.2 horsepower 2200 42.5 lb/hr 476 N-m 1600 37.3 lb/hr N/A N/A N/A N/A TCD3.6L4 CFXT84U L4 3.621 Liters 114.5 2200 43.5 lb/hr 480 N-m 1600 38 lb/hr N/A N/A N/A horsepower N/A TCD3.6L4 CFXT87U L4 3.621 117.9 2200 45.9 lb/hr 500 N-m 1600 40.9 lb/hr N/A N/A N/A Liters horsepower N/A TCD3.6L4 CFXT94U L4 3.621 Liters 127.3 2200 49.3 lb/hr 500 N-m 1600 40.9 lb/hr N/A N/A N/A N/A horsepower TCD3.6L4 CEXT99U 14 3.621 134.1 horsepower 2200 52.7 lb/hr 500 1600 40.9 lb/hr N/A N/A N/A N/A Liters N-m 1,600 TCD3.6L4 CFXT62U L4 3.621 Liters 83.8 horsepower 2200 33.2 lb/hr 360 N-m 29.1 lb/hr N/A N/A N/A N/A

Attachment Last Revised: 4/29/2022